



A28-15 A36-15 A36-30

A series brushless motor

Size	rpm/V	Dia.mm	Length mm	Shaft Dia. mm	Weight g	Cells	working current	max. current	no load current
A28-15-2	4000	28	30	4	86	6-8	5-25	30	4.3
A28-15-4	2000	28	30	4	86	6-12	5-20	25	1.6
A28-15-6	1400	28	30	4	86	6-18	5-15	20	1
A36-15-2	3200	36	38	5	140	6-10	5-35	40	3.3
A36-15-3	2100	36	38	5	140	6-12	5-30	35	2.1
A36-15-4	1600	36	38	5	140	6-18	5-25	30	1.8
A36-30-2	1500	36	54	5	228	6-8	5-35	40	2.5
A36-30-3	1000	36	54	5	228	6-12	5-30	35	1.7
A36-30-4	780	36	54	5	228	6-20	5-25	30	1.1



B20-15 B20-25 B28-25 B36-18

B series brushless motor

Size	rpm/V	Dia.mm	Length mm	Shaft Dia. mm	Weight g	Cells	working current	max. current	no load current
B20-15-12	4100	20	31	2	46	6-18	2-5	6	0.6
B20-15-10	5400	20	31	2	46	6-14	2-6	8	0.7
B20-15-8	6800	20	31	2	46	6-10	3-8	10	1.2
B20-15-6	9200	20	31	2	46				
B20-25-12	2700	20	41	2	67	6-20	2-10	15	0.9
B20-25-10	3200	20	41	2	67	6-14	2-11	17	0.9
B20-25-8	4200	20	41	2	67	6-12	2-13	18	1.2
B20-25-6	5300	20	41	2	67				1.1
B28-25-4	5500	28	47	4	141				3
B28-25-6	3600	28	47	4	141	6-10	5-25	30	1.8
B28-25-8	2700	28	47	4	141	5-16	5-23	28	1.1
B28-25-10	2300	28	47	4	141	6-25	5-20	25	0.9
B36-18-6	4500	35.5	44	4	192	6-10	10-40	50	4.5
B36-18-8	3000	35.5	44	4	192	6-16	5-30	35	2.1
B36-18-10	2300	35.5	44	4	192	6-25	5-25	30	1

Sonderbestellung minimum 10 Wochen Lieferzeit!